

Table Specification for Miro Cube[®] 2

WNC - Tunable White

Type ID	Qty	Manufacturer	COO	Color Temperature	Watts/Voltage	Finish	Mounting	IP Rating	Control
		Rosco	USA	2700K-6500K Can be pre-tuned at factory to CCT: XXXXK	50W/ 100-277V	Die-cast aluminum housing; powder-coated: black - white - custom-colored finish.	Fixture ships with a full yoke attached. 0-10V and DMX data track adapters are also available to be pre-attached at the factory.	IP20	0-10V or DMX RDM via 1, 2, 3 or 4 channels. Control via mobile device using myMIX [®] Connect accessory with the myMIX [®] App.

Table Specification for Miro Cube[®] 2 4C - RGBW

Type ID	Qty	Manufacturer	COO	Color Specifications	Watts/Voltage	Finish	Mounting	IP Rating	Control
		Rosco	USA	3200K-10,000K R: 625nm G: 525nm B: 453nm W: x0.31, y0.32 Can be pre-tuned at factory to CCT: XXXXX, or Hue: XXX Saturation: YYY	50W/ 100-277V	Die-cast aluminum housing; powder-coated: black - white - custom-colored finish.	Fixture ships with a full yoke attached. 0-10V and DMX data track adapters are also available to be pre-attached at the factory.	IP20	0-10V or DMX RDM via 1, 2, 4, 5 or 8 channels. Control via mobile device using myMIX [®] Connect accessory with the myMIX [®] App.

Table Specification for Miro Cube[®] 2 4CA - RGBA

Type ID	Qty	Manufacturer	COO	Color Specifications	Watts/Voltage	Finish	Mounting	IP Rating	Control
		Rosco	USA	3200K-10,000K R: 625nm G: 525nm B: 453nm W: x0.57, y0.42 Can be pre-tuned at factory to CCT: XXXXK, or Hue: XXX Saturation: YYY	50W/ 100-277V	Die-cast aluminum housing; powder-coated: black - white - custom-colored finish.	Fixture ships with a full yoke attached. 0-10V and DMX data track adapters are also available to be pre-attached at the factory.	IP20	0-10V or DMX RDM via 1, 2, 4, 5 or 8 channels. Control via mobile device using myMIX [®] Connect accessory with the myMIX [®] App.

Table Specification for Miro Cube[®] 2 UV365 - Black Light

Type ID	Qty	Manufacturer	COO	UV Output	Watts/Voltage	Finish	Mounting	IP Rating	Control
		Rosco	USA	365nm 10,800m/W	50W/ 100-277V	Die-cast aluminum housing; powder-coated: black.	Fixture ships with a full yoke attached. 0-10V and DMX data track adapters are also available to be pre-attached at the factory.	IP20	0-10V or DMX RDM via 1 channel. Control via mobile device using myMIX [®] Connect accessory with the myMIX [®] App.